Darty A. China Hanan Vayyan Nachinary Equinment Nanufacturing Ca										
Party A: China Henan Yaxuan Machinery Equipment Manufacturing Co.							Quotation date			
Party B: Cl	ient in Ba	angladesh						2024/10/	<b>´10</b>	
Equipment t	ype: 4 row	ws of five-lay	er cages for l	aying he	ens			1	20/60/43	
Chicken hou	use size	Length of chicken house	76. 2	Width of chicken	12. 2	Height of chicken house	4. 85	work unit	meter (classifier)	
				house						
Equipment Spec	ifications	storey	columns	Chickens per door	Per assembly quantity of chickens	Number of cages per row	Total numbe r of group s	Standardized Ioading	Chicken area (cm²/feather)	
Equipment	t data	5	4	8	160	56	224	224 35840 450		
serial number	Product name and specificati on	quantities	work unit (one's workplace)	Unit price (RMB)	Subtotal (dollars)	photograph		note		
0ne、	Cage system	1								
1	five-layer cage netting	224	organize			Cage frame material zinc aluminum magnesium 2.0				
2	Five-layer steel cage frame	224	organize				combined cage frame without welding, cage mesh hot galvanized wire, beautiful and corrosion-resistant stamping molding flat bottom, plate thickness $\geq 1.0$ 2.4 m/root; trough support hot dipped galvanized, p thickness $\geq 1.0$ mm, bolts fixed to the cage frame stepping on the use of firm.		Il and corrosion-resistant, tom, plate thickness $\geqslant$ 1.0 mm;	
3	Galvanized sheet metal egg stopper	224	organize	0					s fixed to the cage frame,	
4	five-tier trough	224	organize							
5	Trough Tray	224	organize					t-dip galvanized, 10/group cage doors with oss sliding doors		

6	water dispenser	224	bend			Square
	Plumbing					V-shaped
7		224	organize			and m
	V-Sink					
8	doser	2	bend			D
			Total cage netting	system:		(RMB)
two、	Feeding sys	tem			I	
1	1 Driving feeder	4	bend			The hopper plate, the ratio is 1: one materia cold-rolled devices.
2	Traction devices and accessories					Including 3 galvanized
3	Car guide rail					3.0 Hot dip
4	Horizontal feeding device					$\Phi$ 140MM gal auger motor
5	Material tower	1	tower			2
			Feeding system	m total:		(RMB)
three	Egg collectio	on system				
1	Egg Picking Machine	Machine Egg collection				Made of zin filter, L-s with an egg 0.75 kW. Sp
2	Egg collection belt		SET			Super long
3	Egg Pickup					New Materia

re hose, conical drinker with

d trough better reduces dripping

makes chicken manure drier

Dosu doser with filter

er is made of zinc-aluminum-magnesium ne Taili motor is 0.75 kW, the speed 1:80, and each hopper is equipped with ial leveler made of hot-dip galvanized ed steel plate 3.0 and two return

304 steel wire rope and hot dip

lip galvanized square tube

alvanized pipe indoor feeding device, or 1.5 kW, total 18 meters auger

20 tons material tower

inc-aluminum-magnesium, soft egg -shaped egg claw, cascade egg picker gg breaking rate of 2‰, and a motor of Speed ratio 1;120

g and durable imported nylon material

ials

	Card					
	· · · · · · · · · · · · · · · · · · ·		Egg collection sy	vstem total: 0		(RMB)
4	Manure cleaning	system				
1	Manure cleaning machine host	4	set			The rubber friction be manure scra cleaning mo 1:120
2	Manure cleaning belt	280	Group			Imported po
3	Accessories	280	Group			Baffle, sup lifting lug
5	Horizontal and oblique manure transport device	21	rice			Each set equipped w pressing ro head is equ manure belt transport r
			Total manure rem	noval svstem:		(rmb)
	Total	environmental cont	trol system and auxiliary		and optimized and	(rmb)
Five		rol system and aux				
1	Fan	18	tower			1.4*1.4m p blades, 1.7
2	Wet curtain	110	Square meter			High permea imported p
3	Wet curtain installatio n accessories	1	Dong			Water pump inlet pipe,
4	Deflector plates and accessories	110	Square meter			Electric a
5	linkage	5	set			Manual and
6	Lighting	6	set	0		Dedicated I to time
	small window for ventilation	60	indivual	0		Frame 1.15n

er coating of the drum increases the between the manure belts, and two crapers are installed. The manure motor is 1.5 kW, with a speed ratio of

polymer material, 1.2mm thick PP tape

support rod (made of galvanized sheet) lug

of horizontal manure cleaning is with a transmission roller, a belt roller, and a tensioning roller. The quipped with a manure scraper, and the elt support rod is T-shaped, which can t manure more efficiently.

push-pull type, stainless steel fan 1.1 kW motor neability, aluminum alloy frame,

pulp, thickness 15cm

np. Return pipe, elbow, direct pipe, be, etc.

automatic opening

nd automatic opening

lighting lines change light according

5mm\*320mm manual and automatic opening

7	7 Microcomput er Intelligent Environment Control System Environment Control System	1	set	00	0		The entire overvoltag failure, l and detern phone at th screen, a temperatur		
	1		Total EMS and ancillary e	quipment:			(RMB)		
VII. Summary									
<b>c</b> ,	Summary of	f costs							
of costs					1				
1									
3	Total costs: (RMB)								
	Above quote	note:The price of	658470RMB is the facto	ry install	ed price	of all equipment.	Does not ind		
freight, does not include tax, does not include equipment installation costs, custome									
	Treight, ad	bes not include tax,	does not include equip	ment inst	allation c	osts, customers ag	ree with the		
	contract ne	egotiation.							
eight	Equipment Engineering Installation Instructions:								
1	The above quotation is valid for 15 days. The labor cost for foreign installation guidance is 100 US								
2	The above quotation does not include cables other than equipment, which need to be prepared by custom								
-	Before installation, Party B needs to provide an air compressor, and the front and rear ends of the ch								
3	with power supplies and installation cables。								
4	If the company needs to arrange the installation, please arrange the accommodation and meals for the install								
	When installing the equipment, Party B must appoint two full-time personnel to accompany the installa								
5	the normal operation, operation and maintenance of the equipment.								
L	1								

re system of 18 wind turbines (overload, age, undervoltage, phase loss, inverter line breaks, etc., can be timely alarm, ermine the direction of the fault) cell the same time to receive a 10-inch touch a small window to control outdoor cure compensation

nclude invoice, does not include the initial price, details signed

JS dollars per person per day.

omers.

chicken house need to be equipped

lers according to the situation.  ${\scriptstyle \circ}$ 

ation and training to facilitate

Nine	Company address, contact information and service phone number: 008613917849689; Email: landiii@foxma
	Whatapp: https://wa.me/13917856548
1	

nail.com